

MAVERICK

engineering

MACHINE SPECIFICATIONS As at 22 July 2011		1 Lane
		SUPer MACHINE
1	Bag/Pouch Type	SUPerPouch™ SUPerJug™
2	Bag Size Range	1,5LT - 5LT
3	Selection (suitable for max. output bags per month)	850 000
4	General Output: 2LT to 5LT bags per hour	1350
5	10LT to 25LT bags per hour	-
6	220LT bags per hour	-
7	Material Web Width (maximum)	600mm
8	Material Roll Diameter (maximum)	600mm
9	Index Accuracy/Draw Length Accuracy	+/- 2mm
10	Side Track Accuracy/Web Guide Accuracy	+/- 2mm
11	Compact Material Loading Gantry	-
12	4 Reel Driven Unwind System: Configuration	1 reel ÷ 2
13	Reel Core Shafts (76mm or 152mm) 2 are spare for pre-load	Optional
14	Web Edge Guide System (side tracking of film)	Manual
15	Static Induction (to cling webs\minimise air in between layers)	No
16	Dancer Arm Accumulator System (tension control)	Yes
17	Independent Servo Driven Draw (pull) Roller Stations	3
18	Hole Punch & Cut Out / Waste Removal	Catch Bag
19	Web Splice Detection Unit	No
20	Gland Feed Bowl	1
21	Gland Bulk Storage Bin (for up to std 1" fitments)	1
22	Automatic Tap, Cap Unit (cost includes std number of tap types)	2
23	Tap Vibratory Bowl	1
24	Tap Bulk Storage Bin	1
25	Side Seal Station: Effective sealing length	Shaped
26	Cross Seal Station: Effective sealing length	600mm
27	Delta / Shaped Corner Seal Unit	No
28	Combination Rotary Perforator and/or Cut Off Unit	No
29	Delivery Table(s) (with stacking assist*)	No
30	Web Spreader Unit Sets Included	No
31	Coding / Dating / Marking Equipment Included	Not Available
32	Modem Link (direct communication facility)	No
33	CE Rating (safety rating)	Yes
34	Light Curtain (additional machine perimeter safety) Included	Yes
35	Operator Manual, Program, Drawings, Instructions	Yes
36	Key Spares Included	Yes
37	Warranty (months) from date of installation (parts & labour)	12
38	Delivery from date of order (weeks)	21
39	Machine "footprint" area required length x width (approx)	14m x 4,0m
40	Machine Electrical Power Requirements (380V,3-Phase,50HZ)	30KVA
41	Air requirements (approx): - Output free air delivery	2000L/min
	- Operating pressure	5 BAR
	- Motor power	20KW